

Caster Wheels

AGV Universal Wheel

ATOMBOTIX

1.



2.



3.



4.



5.



6.



7.



8.



Antistatic Design



Reduces static electricity, enhancing operational safety

Dual-wheel



Smooth rotation and better maneuverability

Elastic Performance



High-resilience polyurethane for long-lasting flexibility

Floor-safe



Gentle on surfaces, no damage to floors

Silent & Wear-resistant



Low noise, abrasion resistance, and no color fading

Rust-resistant Core



Protected aluminum or cast iron hub

AGV Universal Wheel

#	1	2
Part No.	AB-UW-D25-C30	AB-UW-D57-C100
Tread Material	PU 55D	PU 93A
Hub Material	PU 73A	Aluminum
Wheel Dia(mm)	25	57
Wheel Wid(mm)	15	14×2
Total Height(mm)	37	80
Radius(mm)	16	22
Top Plate(mm)	30×38	67×49
Bolt Hole Centers(mm)	29×21	52×35
Attaching Bolt Size(mm)	4	8
Max. Load Capacity(kg)	30	100

#	3	4
Part No.	AB-UW-D50-C150	AB-UW-D55-C200
Tread Material	PU 93A	PU 93A
Hub Material	Aluminum	Aluminum
Wheel Dia(mm)	50	55
Wheel Wid(mm)	20×2	20×2
Total Height(mm)	82	79
Radius(mm)	20	20
Top Plate(mm)	111×80	84×84
Bolt Hole Centers(mm)	87/78×60	64/59×64/59
Attaching Bolt Size(mm)	9	9
Max. Load Capacity(kg)	150	200
#	5	6
Part No.	AB-UW-D65-C200	AB-UW-D76S-C150
Tread Material	PU 93A	PU 73A
Hub Material	Aluminum	Aluminum
Wheel Dia(mm)	65	76
Wheel Wid(mm)	24×2	24×2
Total Height(mm)	87	107
Radius(mm)	20	20
Top Plate(mm)	111×80	104×82
Bolt Hole Centers(mm)	87/78×60	87/78×60
Attaching Bolt Size(mm)	9	9
Max. Load Capacity(kg)	200	150
#	7	8
Part No.	AB-UW-D76S-C200	AB-UW-D76-C200
Tread Material	PU 93A	PU 73A
Hub Material	Aluminum	Aluminum
Wheel Dia(mm)	76	76
Wheel Wid(mm)	24×2	24×2
Total Height(mm)	107	107
Radius(mm)	20	20
Top Plate(mm)	104×82	110×85
Bolt Hole Centers(mm)	87/78×60	86×60
Attaching Bolt Size(mm)	9	9
Max. Load Capacity(kg)	200	200

9.



10.



11.



12.



13.



14.



#	9	10
Part No.	AB-UW-D76-C150	AB-UW-D76-C300
Tread Material	PU 73A	PU 93A
Hub Material	Aluminum	Aluminum
Wheel Dia(mm)	76	76
Wheel Wid(mm)	24×2	30×2
Total Height(mm)	107	110
Radius(mm)	20	22
Top Plate(mm)	110×85	116×110
Bolt Hole Centers(mm)	86×60	92/76×76/67
Attaching Bolt Size(mm)	9	11
Max. Load Capacity(kg)	150	300
#	11	12
Part No.	AB-UW-D80-C500	AB-UW-D100-C600
Tread Material	PU 93A	PU 55D
Hub Material	Steel 45#	Iron
Wheel Dia(mm)	80	100
Wheel Wid(mm)	35×2	35×2
Total Height(mm)	110	133
Radius(mm)	21	21
Top Plate(mm)	116×100	116×100
Bolt Hole Centers(mm)	78×78	78×78
Attaching Bolt Size(mm)	9	9
Max. Load Capacity(kg)	500	600
#	13	14
Part No.	AB-UW-D150-C1000	AB-UW-D200-C1500
Tread Material	PU 55D	PU 55D
Hub Material	Iron	Iron
Wheel Dia(mm)	150	200
Wheel Wid(mm)	40×2	40×2
Total Height(mm)	191	268
Radius(mm)	45	57
Top Plate(mm)	159×115	185×135
Bolt Hole Centers(mm)	133/125×86/62	155/132×105/85
Attaching Bolt Size(mm)	14	14
Max. Load Capacity(kg)	1000	1500

